



ILLUMINATION

- Ultra-bright, energy efficient, long-lasting white LEDs provide uniform illumination.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Mounting canopy included for top or end mount.
- Universal knockout pattern on backplate for wall mount.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations (0° – 50°C).
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Meets city of Chicago requirements.
- Certified to CEC under Title 20 Regulations.

HOUSING

- Durable, powder-coated 20-gauge steel construction in white or black finish.
- Unique design allows double face conversion in the field.
- Field removable steel knockout Chevron directional indicators.

ORDERING INFORMATION

ITEM NUMBER	No. of FACES	LETTER	HOUSING	BATTERY	OPTIONS
DZ-CAXTEU	1 - Single Face	R-Red on White	W-White	(blank)-AC-Only	NA - Exit No Arrow S - NA - Stair No Arrow
	2 - Universal Single/Double Face		B-Black	EM-Battery Backup	-DA - Exit Double Arrow -S-DA - Stair Double Arrow
					-RA ¹ Exit Right Arrow -S-RA ¹ - Stair Right Arrow
					LA ¹ - Exit Left Arrow -S-LA ¹ - Stair Left Arrow
					-LARA ² - Exit Left/Right Arrow
					-S-LARA ² - Stair Left/Right Arrow

Due to continuous improvements, the information herein may be changed without notice

DIMENSIONS

