



OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C-120V/2C-277V: Dual circuit option on the AC-only unit enables it to be connected to two different power supplies at the same time.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- Custom: Signs available with requested "special" wording.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (-20°C – 50°C).
- Certified to CEC under Title 20 Regulations.

HOUSING

- 5VA flame retardant, UV-stabilized polycarbonate in white, black or gray finish.
- High-impact resistant, UV-stabilized polycarbonate clear lens.
- Corrosion-resistant enclosure with engineering grade silicone gasket.
- Knockouts provided for conduit feed applications.
- EZ snap-out Chevron directional indicators .

ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING


- Polycarbonate mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

ORDERING INFORMATION

ITEM NUMBER	No. of FACES	LETTER COLOR	HOUSING COLOR	FACE PANEL	BATTERY	OPTIONS
DZ-WLEZXTEU	1 - Single Face	R-Red	W - White	W-White	(blank)-AC-Only	SDT- Self-Diagnostics ¹
	2 - Double Face	G-Green	B - Black	B-Black	EM-CW-Battery Backup (Cold Weather)	2C-120- Dual Circuit with 120V input ²
			G - Gray	A-Aluminum		2C-277- Dual Circuit with 277V input ²
						TP - Tamper-Proof
						USA- Assembled In USA

Due to continuous improvements, the information herein may be changed without notice

DIMENSIONS



ELECTRICAL INFORMATION	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
DZ-WLEZXTEU-RED/GREEN	2.7	2.7	0.025	0.011
DZ-WLEZXTEU-RED/GREEN/EM/SDT	3.3	3.4	0.030	0.014
DZ-WLEZXTEU-RED/GREEN-2C	2.4	2.4	0.023	0.011